

# Christie Matrix StIM WUXGA

Technical specifications		Christie Matrix StIM™ WUXGA – (1920 x 1200) single DMD – Part number: 125-001113-XX
Image	brightness	• 600 lumens ANSI ±10% (rated at 75-80% EBU depending on the lens)
	contrast	• 10,000:1 dynamic contrast (under LED control) • No mechanical iris required
	uniformity	• 95% brightness and color uniformity after electronic adjustment
Display technology	type	• Revolutionary solid state projector using a single TI Darkchip 3™ DMD with a solid state illumination engine (no color wheel) and sealed optics
	native resolution	• Native 1920 x 1200 (16:10 aspect ratio) WUXGA
Input	signals	• Up to 1920 x 1200 WUXGA (Native 1920 x 1200 recommended)
	scan rates	• Horizontal: 15-150KHz • Vertical: 23.97-120Hz
Inputs/ outputs, control and networking	inputs	• Dual DVI-D and HD15 analog inputs standard • On-board Ethernet control capabilities (ChristieNET™ functionality) • Additional Ethernet connections for Christie ArrayLOC™ network • IR/wired remote control as part of optional user kit • 2 RS-232 ports and 1 RS-422 port
	optional	• Analog input card • DVI-I input card • HD-SDI input card
Optical system	lens mount	• Mechanical, horizontal and vertical lens shift • No shutter required • No iris required – user programmable illumination parameters (eliminates the need for a mechanical shutter)
	illumination	• Full spectrum InfraRGB™ (RGB + IR LEDs) • Illumination package has a MTBF of 50,000 hrs • Light module can be changed in 15 minutes and is color and bright level matching in real-time to the projector array
	ArrayLOC	• Manages the brightness and color levels of all projectors within an array to a common level, in real-time with no additional latency
Lenses	fixed	• 0.64:1 WUXGA fixed IR and visible light optimized lens • 0.75:1 fixed IR and visible light optimized lens
	zoom	• 1.2-1.6:1 WUXGA zoom IR and visible light optimized lens
	offsets	• 0.64:1 lens features ±5% (horizontal) and ±5% (vertical) offset when mounted in landscape orientation • 0.75:1 lens features ±80% (horizontal) and ±100% (vertical) offset when mounted in landscape orientation • 1.2-1.6:1 lens features ±80% (horizontal) and ±100% (vertical) offset when mounted in landscape orientation <sup>1</sup>
Accessories	standard	• Line cord
	optional	• Analog RGBHV input card • DVI-I input card • HD-SDI input card • Remote IR sensor • User kit (includes manual, IR remote) • Rugged Motion Platform user kit (purpose-built)
Enhanced feature sets	• Minimum Processing Latency (MPL™) • Christie Twist™ II – Advanced warping/edge-blending hardware technology integrated directly into the projector, includes warping/blending software • Auto setup, power up • Menus in 5 languages • AccuFrame adjustable to <6ms • Multiple channel memories (for recall memory storage) • Christie ArrayLOC – automatic, continuous management of brightness and color space levels of all projectors in the array to a common level, in real-time • Christie InfraScene™ – the capability of the simultaneous, independent display of both visible light and infrared projection • Dual-channel compositing modes including InfraScene and 120Hz interleaved mode	
Power requirements	operating voltage	• 100-240 VAC 50/60Hz
	operating current	• 5.3A
	dissipation	• 1364 BTU/hr
Physical	size	• Projector head module + light module (no lens): 8.7 x 18.4 x 11.0" (220 x 467 x 287mm) • Electronics module: 16.5 x 5.5 x 6.7" (420 x 140 x 170mm)
	weight	• Projector head module + light module (no lens): 32lbs (14.6kg) • Electronics module: 9.7lbs (4.4kg)
	shipping weight	• 52lbs (23.6kg)
Noise	• 38dBA at 25°C ambient temperature (without electronics module)	
Environment	• Temperature: 40-95°F (5-35°C) • Humidity: 20-80% non-condensing	
Regulatory approvals	• Directives (EC) 2011/65/EU (RoHS) • 2012/19/EU (WEEE) • Regulation (EC) No. 1907/2006 (REACH) • CAN/CSA C22.2 No. 60950-1 • UL 60950-1 • IEC 60950-1 • FCC, Part 15, Subpart B, Class A • EN55022/CISPR22 Class A • EN55024 / CISPR24 • Certifications marks (check with Christie for latest update): cULus (Canada & US), CE (EU), CCC (China), GoST-R (Russia), KC (Korea), PSE (Japan), C-Tick (Australia & New Zealand)	
Warranty	• Two years parts and labor • Contact an authorized Christie representative for full details of our limited warranty	

<sup>1</sup>Each offset is specified with the other at zero. Simultaneous horizontal and vertical offsets may limit the adjustment range of each.

## Ruggedized/Build to order

Several of our models will be available on a build to order basis and may include ruggedization for use on motion platforms. For details, please contact your Christie sales representative.

### Corporate offices

Christie Digital Systems USA, Inc.  
USA – Cypress  
ph: 714 236 8610

Christie Digital Systems Canada Inc.  
Canada – Kitchener  
ph: 519 744 8005

### Worldwide offices

Australia  
ph: +61 (0) 7 3624 4888

Brazil  
ph: +55 (11) 2548 4753

China (Beijing)  
ph: +86 10 6561 0240

China (Shanghai)  
ph: +86 21 6278 7708

Eastern Europe and  
Russian Federation  
ph: +36 (0) 1 47 48 100

France  
ph: +33 (0) 1 41 21 44 04

Germany  
ph: +49 2161 664540

India  
ph: +91 (080) 6708 9999

Japan (Tokyo)  
ph: 81 3 3599 7481

Korea (Seoul)  
ph: +82 2 702 1601

Republic of South Africa  
ph: +27 (0)11 510 0094

Singapore  
ph: +65 6877 8737

Spain  
ph: +34 91 633 9990

United Arab Emirates  
ph: +971 4 3206688

United Kingdom  
ph: +44 (0) 118 977 8000

**Independent sales  
consultant offices**

Italy  
ph: +39 (0) 2 9902 1161



ISO 9001  
ISO 14001

Kitchener, Ontario



For the most current specification information, please visit [www.christiedigital.com](http://www.christiedigital.com)



Copyright 2014 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 3869 Jul 14

**CHRISTIE®**