

Christie Mirage WU7K-J

| Christie Mirage WU7K-J – WUXGA (1920 x 1200) – 3-chip DLP® – Part number: 132-006129-XX | | |
|-----------------------------------------------------------------------------------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image | brightness | • 6300 ANSI lumens (6950 center lumens) @ 200-240V ±10% • 4750 ANSI lumens (5200 center lumens) @ 100-120V ±10% |
| | contrast | • 1600-2000:1 full field • 650:1 ANSI (typical) |
| | uniformity | • 80% brightness uniformity |
| Display | type | • 3-chip 0.96" DMD |
| | native resolution | • WUXGA (1920 x 1200) |
| | frame delay | • As low as one frame |
| Lamp | type | • 1kW CERMAX® Xenon pre-aligned lamp module |
| | estimated life | • 1500 hrs |
| Input | standard | • Slot 1-2 populated, standard: two Dual Link DVI-D (330 MHz) input cards (each has VGA (165 MHz) for 3D or dual input 3D compatibility) with HDMI 1.3 receiver • Slot 3-4 unpopulated |
| | optional | • Analog BNC • Dual-link DVI • SD/HD-SDI • Video Decoder • Twin HDMI • DMX512 interface card |
| | signals | • HDTV formats VGA through to WQXGA (2560 x 1600) • Accepts all current 2D HDTV/DTV formats (optional input module may be required) • HDMI 1.3 receiver supports mandatory HDMI 1.4a 3D modes of operation plus 24-144Hz triple flash 3D mode • Multi-standard video decoder • Horizontal and vertical scaling, all inputs |
| | pixel clock | • 330 MHz |
| | scan rates | • Horizontal: 15-120kHz • Vertical: 23.97-150Hz (frame lock maximum 120Hz) • 48-60Hz frame doubled or dual input 3D • 96-120Hz frame rate up to 1920 x 1200 • 24-144Hz triple flash 3D |
| Inputs/outputs, control and networking | | • RS-232 in/out • RS-422 in • Ethernet (10/100) • GPIO (RS-232 9 Pin male connector) • Built-in backlit LCD keypad • Remote control (with optional wired XLR connection) |
| Optical system | | • Dust-sealed 3-chip DMD light engine • Motorized horizontal and vertical lens offset • Scheimpflug/Boresite (tilt) adjustment • Built-in light shutter • Tool-free lens insertion system |
| Lenses | fixed | • 0.67:1 HD/WU ILS Lens* • 1.1:1 HD/WU ILS Lens |
| | zoom | • 1.16-1.49:1 HD/WU ILS Lens** • 1.4-1.8:1 HD/WU ILS Lens • 1.8-2.6:1 HD/WU ILS Lens • 2.6-4.1:1 HD/WU ILS Lens • 4.1-6.9:1 HD/WU ILS Lens • 6.9-10.4:1 HD/WU ILS Lens |
| | offsets ¹ | • All lenses ±112% Vertical ±42% Horizontal except those noted below * 0.67:1 fixed lens ±22%V ±6%H ** 1.16-1.49 zoom lens ±82%V ±38%H |
| Accessories | standard | • IR remote • Power cord • GPIO 3D sync cable |
| | optional | • ILS lens adapter kit • CT lens mount • Yellow notch filter • Fog filters • Ceiling mount • Ceiling mount extension • Remote IR sensor |
| Enhanced feature sets | | • Embedded Christie Twist™ • Intelligent Lens System (ILS™) • Advanced block artifact reduction • ChristieNET™ web interface • User-friendly, intuitive LCD keypad • Lamp memory module • User replaceable lamps • Advanced 10-bit processing • Automatic shut-off • Dust-sealed light engine • SNMP (simple network management protocol) • DHCP (dynamic host configuration protocol) • Hybrid stack • Compatibility with many legacy accessories |
| Power requirements | operating voltage | • 100-240 VAC 50/60Hz |
| | operating current | • 12A @ 100-120V • 8A @ 200-240V |
| | power | • 1600W |
| | dissipation | • 5460 BTU/hr |
| Dimensions | size | • (LxWxH): 22.3 x 26.0 x 12.9" (566 x 660 x 328mm) |
| | shipping size | • (LxWxH): 33.5 x 30.0 x 26.0" (851 x 726 x 660mm) |
| | weight | • 88lbs (40kg) (without lens) |
| | shipping weight | • 125lbs (57kg) |
| Operating environment | | • Temperature: 40-104°F (5-40°C) • Humidity: 20-80% non-condensing |
| Regulatory approvals | | • Directives (EC) 2002/95/EC (RoHS); 2002/96/EC (WEEE); Regulation (EC) No. 1907/2006 (REACH) • CAN/CSA C22.2 No. 60950-1 • UL 60950-1 • IEC 60950-1 • FCC, Part 15, Subpart B, Class A • EN55022/CISPR22 Class A • EN55024/CISPR24 • Certifications marks (check with Christie for latest update): cULus (Canada & US), CE (EU), CCC (China), GoST-R (Russia), KC (Korea), PSE (Japan), C-Tick (Australia & New Zealand), South Africa |
| Limited warranty | | • Three years parts and labor (including light engine) • Contact an authorized Christie representative for full details of our limited warranty |

¹ Values are for reference and should be validated with the Christie lens calculator.

Corporate offices

Christie Digital Systems USA, Inc
USA – Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Canada – Kitchener
ph: 519 744 8005

Worldwide offices

United Kingdom
ph: +44 (0) 118 977 8000

Germany
ph: +49 2161 664540

France
ph: +33 (0) 1 41 21 44 04

Spain
ph: +34 91 633 9990

Eastern Europe and
Russian Federation
ph: +36 (0) 1 47 48 100

United Arab Emirates
ph: +971 (0) 4 299 7575

India
ph: (080) 41468940

Singapore
ph: +65 6877 8737

China (Shanghai)
ph: +86 21 6278 7708

China (Beijing)
ph: +86 10 6561 0240

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161

South Africa
ph: +27 (0) 317 671 347



For the most current specification information, please visit www.christiedigital.com

Copyright 2011 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 3066 Sept 11

CHRISTIE